SOUTH CONDUIT
CONDUIT AND ACCESSORIES

Catalog No.: _____
Job/Title: _____

2” Galvanized Nipples (GRC)

South Conduit RIGID is hot-dipped galvanized inside and out. It is top-coated with a compatible organic layer to inhibit white rust and increase corrosion resistance.

FULL CODES AND STANDARDS COMPLIANCE

South Conduit RIGID is U.L. listed . It meets Underwriters Laboratories Safety Standard U.L. 6. South Conduit RIGID is recognized as an equipment grounding conductor by NEC Article 250. Documentation for compliance with Article 250-2 of the 1999.

Length	Size	Item Number
2”	CL GRC Nipple	12000
2”	2-1/2” GRC Nipple	12025
2”	3” GRC Nipple	12030
2”	3-1/2” GRC Nipple	12035
2”	4” GRC Nipple	12040
2”	4-1/2” GRC Nipple	12045
2”	5” GRC Nipple	12050
2”	6” GRC Nipple	12060
2”	7” GRC Nipple	12070
2”	8” GRC Nipple	12080
2”	9” GRC Nipple	12090
2”	10” GRC Nipple	12010
2”	12” GRC Nipple	12012
2”	18” GRC Nipple	12018
2”	24” GRC Nipple	12024

- Low Conductivity, High Corrosion Resistance
- Smooth Defect-Free Interior and Exterior
- Galvanized Steel

South Conduit
6315 Traffic Avenue, Ridgewood, NY 11385 | 718.257.2111

c UL us LISTED